## **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions and listings of claims in the application:

## LISTING OF CLAIMS:

- 1.-12. (canceled).
- 13. (previously presented): The thin film transistor substrate according to claim 29, wherein said impurity doping regions formed in a self-aligning manner are formed so as to overlap said first gate electrode by 0.1 μm or less.
- 14. (previously presented): The thin film transistor substrate according to claim 29, wherein at least one of said impurity doping regions formed in a self-aligning manner with respect to said first gate electrode includes an LDD structure.
  - 15. (canceled).
- 16. (previously presented): The thin film transistor substrate according to claim 29, wherein at least one of impurity doping regions which overlap said second gate electrode includes an LDD structure.

17.-28. (canceled).

29. (currently amended): A thin film transistor substrate comprising: an insulating substrate;

a first low voltage driving thin film transistor formed above said insulating substrate, wherein said low voltage driving first thin film transistor comprises a first active layer formed above said insulating substrate, a first gate insulating film formed on said first active layer, and a first gate electrode driven at low voltage formed on said first gate insulating film; and

a second-high voltage driving thin film transistor formed above said insulating substrate, wherein said high voltage driving second thin film transistor comprises a second active layer formed above said insulating substrate, and a second gate insulating film formed on said second active layer, a second gate electrode driven at high voltage formed on said second gate insulating film,

wherein a thickness of said second gate insulating film is larger than a thickness of said first gate insulating film comprises said first gate insulating film and a gate cover film formed above said first gate insulating film,

wherein said second active layer has at least two impurity doping regions which overlap said second gate electrode,

wherein said first active layer has at least two impurity doping regions formed in a self aligning manner with respect to said first gate electrode, wherein said second high voltage driving thin film transistor further comprises a third gate electrode driven at low voltage, wherein a gate length of said third gate electrode is shorter than a gate length of said second gate electrode, wherein said third gate electrode is formed between said second active layer and said second gate electrode and on the first gate insulating film;

wherein said third gate electrode is formed of the same material as said first gate electrode, and

wherein said third gate electrode has the same thickness as said first gate electrode.

30. (currently amended): A-The thin film transistor substrate according to claim 29 comprising:

an insulating substrate;

a first thin film transistor formed above said insulating substrate, wherein said first thin film transistor comprises a first active layer formed above said insulating substrate, a first gate insulating film formed on said first active layer, and a first gate electrode formed on said first gate insulating film; and

a second thin film transistor formed above said insulating substrate, wherein said second thin film transistor comprises a second active layer formed above said insulating substrate, and a second gate insulating film formed on said second active layer, a second gate electrode formed on said second gate insulating film,

wherein a thickness of said second gate insulating film is larger than a thickness of

said first gate insulating film,

wherein said second active layer has at least two impurity doping regions which overlap said second gate electrode,

wherein said first active layer has at least two impurity doping regions formed in a self aligning manner with respect to said first gate electrode,

wherein said second thin film transistor further comprises a third gate electrode formed between said second active layer and said second gate electrode, and

wherein said impurity doping regions which overlap said second gate electrode are formed so as to overlap said second gate electrode by 2.0 µm or less.

31. (currently amended): A-The thin film transistor substrate according to claim 29comprising:

an insulating substrate;

a first thin film transistor formed above said insulating substrate, wherein said first thin film transistor comprises a first active layer formed above said insulating substrate, a first gate insulating film formed on said first active layer, and a first gate electrode formed on said first gate insulating film; and

a second thin film transistor formed above said insulating substrate, wherein said second thin film transistor comprises a second active layer formed above said insulating substrate, and a second gate insulating film formed on said second active layer, a second gate electrode formed on said second gate insulating film,

wherein a thickness of said second gate insulating film is larger than a thickness of said first gate insulating film,

wherein said second active layer has at least two impurity doping regions which overlap said second gate electrode,

wherein said first active layer has at least two impurity doping regions formed in a self aligning manner with respect to said first gate electrode,

wherein said second thin film transistor further comprises a third gate electrode formed between said second active layer and said second gate electrode, and

wherein said third gate electrode comprises a two-layer structure including a semiconductor layer and a metal or a metal silicide layer.

- 32. (previously presented): The thin film transistor substrate according to claim 29, wherein said second gate electrode comprises a semiconductor layer.
- 33. (currently amended): The thin film transistor substrate according to claim 29, wherein said second gate insulating film comprises said first insulating film and a gate cover film formed above said first gate insulating film

wherein said third gate electrode is formed of the same material as said first gate electrode, and

wherein said third gate electrode has the same thickness as said first gate electrode.

Attorney Docket No.: Q77321

34. (previously presented): The thin film transistor substrate according to claim 29, wherein said first gate electrode, said second gate electrode and said third gate electrode are formed under wires which connect to said impurity doping regions.